



221120341058

副本

浙江中一检测研究院股份有限公司

ZHEJIANG ZHONGYI TEST INSTITUTE CO.,LTD

检测报告

Test Report

报告编号: HJ233914

Report No.

项目名称 宁波上中下自动变速器有限公司土壤和地下水自行监测
 Project name

委托单位 宁波上中下自动变速器有限公司
 Client

委托单位地址 宁波北仑区滨海新城春晓大道
 Address



检测单位 (盖章)

Detection unit (seal)



编制人 李梦洁 李梦洁

Compiled by

审核人 宋莉 宋莉

Inspected by

批准人 王雪 王雪

Approved by

报告日期 2023-12-06

Report date

浙江中一检测研究院股份有限公司 ZHEJIANG ZHONGYI TEST INSTITUTE CO.,LTD

地址 Address:浙江省宁波市高新区清逸路 69 号 C 幢

邮编 Post Code:315040

电话 Tel:0574-87908555 87837222 87836111

传真 Fax: 0574-87835222

网址 Web: www.zynb.com.cn

Email: zyjc@zynb.com.cn

检测声明

Test report statement

- 1、本机构保证检测工作的公正性、独立性和诚实性，对检测的数据负责。
We ensure the testing data impartiality, independence and integrity, and responsible for the testing data.
- 2、本报告不得涂改、增删。
The report shall not be altered, added and deleted.
- 3、本报告无公司检验检测专用章无效。
The report is invalid without “The Special Stamp for Inspection & Test Report”.
- 4、本报告无审核人、批准人签名无效。
The report is invalid without the verifier and the approver.
- 5、本报告只对采样/送检样品检测结果负责。
The results relate only to the items tested.
- 6、对本报告有疑议,请在收到报告 15 天内与本公司联系。
Please contacts with us within 15 days after you received this report if you have any questions with it .
- 7、未经本公司书面允许，对本检测报告局部复印无效，本单位不承担任何法律责任。
The local copy of the report is invalid without prior written permission of our unit, our company will not bear any legal responsibility.
- 8、本报告未经同意不得作为商业广告使用。
The reports shall not be published as advertisement without the approval of us.
- 9、委托方要求对检测结果进行符合性判定时，如无特殊说明，本公司根据委托方提供的标准限值，采用实测值进行符合性判定，不考虑不确定度所带来的风险，据此判定方式引发的风险由委托方自行承担，本公司不承担连带责任。
When the client requests the conformity judgment of the test results,if there is no special instructions,the company will use the actual measured value to make the conformity judgment according to the evaluation standards provided by the client, and the risk arised by the uncertainty is not considered. The risks caused are borne by the entrusting party, and the company does not bear joint liability.

检测说明

Test Description

样品类别 Sample type	土壤、地下水	检测类别 Type	委托检测
采样日期 Sampling date	2023-11-23	检测日期 Testing date	2023-11-23~2023-11-30
采样地址 Sampling address	宁波北仑区滨海新城春晓大道		
检测地点 Testing address	浙江中一检测研究院股份有限公司及采样现场		
采样方法 Sampling Standard	土壤环境监测技术规范 HJ/T 166-2004 地下水环境监测技术规范 HJ 164-2020		
评价标准 Evaluation standard	土壤执行《土壤环境质量建设用地土壤污染风险管控标准（试行）》（GB 36600-2018）表 1 及表 2 中第二类用地筛选值标准限值；地下水执行《地下水质量标准》（GB/T 14848-2017）表 1 及表 2 中IV类标准限值，其中可萃取性石油烃（C ₁₀ -C ₄₀ ）执行《上海市建设用地土壤污染状况调查、风险评估、风险管控与修复方案编制、风险管控与修复效果评估工作的补充规定（试行）》中第二类用地筛选值。		
备注 Note	1、检测点位、检测项目、检测频次、检测依据、标准限值依据由委托单位指定，检测频次不满足评价标准规定要求时，检测结果不能直接作为评价是否达标的依据。 2、“<”表示该项目（参数）的检测结果小于检出限。		

检测结果

Test Conclusion

表 1、土壤检测结果

检测点位	土壤深度 m	样品性状	检测结果 mg/kg (pH 值无量纲)		
			pH 值	镍	石油烃 (C ₁₀ -C ₄₀)
4#1A01	0-0.5	灰色	8.57	20	20
	2.0-2.5	灰色	7.96	39	9
	3.0-4.0	灰色	8.47	35	11
5#1B01	0-0.5	棕黄色、灰白色	8.22	18	8
	2.0-2.5	棕黄色、灰白色	8.27	24	43
	2.0-2.5 (平行)	棕黄色、灰白色	8.19	23	46
	3.0-4.0	灰色	7.99	35	15
6#1C01	0-0.5	棕黄色	7.78	26	35
	2.0-2.5	棕黄色	8.27	42	17
	4.0-5.0	灰色	8.10	39	13
7#1D01	0-0.5	棕黄色	8.34	26	10
	0-0.5 (平行)	棕黄色	8.27	24	10
	2.0-2.5	棕黄色	8.46	36	9
	4.0-5.0	灰色	7.81	34	8
标准限值			—	≤900	≤4500

表 2、地下水检测结果


检测点位	样品性状	检测结果 mg/L (pH 值 无量纲)			
		pH 值	铝	镍	可萃取性石油烃 (C ₁₀ -C ₄₀)
1#2B01	浅黑微浑	7.7	0.010	4.7×10 ⁻⁴	0.40
2#2C01	无色微浑	7.5	<0.009	4.1×10 ⁻⁴	0.03
2#2C01 (平行)	无色微浑	7.5	<0.009	3.2×10 ⁻⁴	0.05
3#2D01	无色微浑	6.9	<0.009	3.4×10 ⁻⁴	0.02
标准限值		5.5≤pH<6.5 8.5<pH≤9.0	≤0.50	≤0.10	≤1.2

表 3、土壤检测项目、检出限、检测依据及主要检测仪器

检测项目	检出限	检测依据	主要检测仪器
pH 值	—	土壤 pH 值的测定 电位法 HJ 962-2018	pH 计
镍	3mg/kg	土壤和沉积物 铜、锌、铅、镍、铬的测定 火焰原子吸收分光光度法 HJ 491-2019	原子吸收分光光度计
石油烃 (C ₁₀ -C ₄₀)	6mg/kg	土壤和沉积物 石油烃 (C ₁₀ -C ₄₀) 的测定 气相色谱法 HJ 1021-2019	气相色谱仪

表 4、地下水检测项目、检出限、检测依据及主要检测仪器

检测项目	检出限	检测依据	主要检测仪器
pH 值	—	水质 pH 值的测定 电极法 HJ 1147-2020	pH 计
铝	0.009mg/L	水质 32 种元素的测定 电感耦合等离子体发射光谱法 HJ 776-2015	等离子体原子发射光谱仪
镍	6 × 10 ⁻⁵ mg/L	水质 65 种元素的测定 电感耦合等离子体质谱法 HJ 700-2014	电感耦合等离子体质谱仪
可萃取性石油烃 (C ₁₀ -C ₄₀)	0.01mg/L	水质 可萃取性石油烃 (C ₁₀ -C ₄₀) 的测定 气相色谱法 HJ 894-2017	气相色谱仪



附表（注：点位坐标由 RTK 仪测定，水位等于井口（海拔或高程）减埋深计算所得，数据仅供参考。）

1、RTK定位信息表

采样点位	RTK 定位（CGCS2000 国家大地坐标系）（WGS84 地球坐标系）	
	东经	北纬
2B01	121° 53' 30.24868''	29° 44' 59.09251''
2C01	121° 53' 29.81109''	29° 44' 57.03141''
2D01	121° 53' 39.49383''	29° 45' 01.58514''
1A01	121° 53' 32.43244''	29° 45' 01.31112''
1B01	121° 53' 30.85101''	29° 44' 57.82953''
1C01	121° 53' 29.76799''	29° 44' 56.97521''
1D01	121° 53' 39.52682''	29° 45' 01.55733''

2、水位信息表

采样点位	地面高程 m	埋深 m	水位 m
2B01	17.077	3.25	13.83
2C01	17.112	2.69	14.42
2D01	16.638	2.45	14.19